



**JUST
PLUG IT
IN...**

**AND
READ!**

**Cherry dependability...in an alphanumeric display that's
readable in sunlight, any light ... and installs in seconds**

Excellent brightness, full half-inch characters, 7-bit ASCII input and simple plug-in installation make the Cherry gas discharge display the right choice for you. Surprising versatility in a small package—

adjustable brightness, flashing display and blank panel modes, fully addressable cursor, custom designs, too. Call or write today for complete technical literature or a full demonstration.

Take a closer look:

2 simple plugs are the only hook-up required.

Only one voltage (12VDC) required.

Selectable baud rate with RS232C or TTY standard.

5 adjustable brightness levels.
16 or 20 characters long.



GAS DISCHARGE DISPLAYS

CHERRY ELECTRICAL PRODUCTS CORP. 3609 Sunset Avenue, Waukegan, IL 60085—312/689-7700—TWX 910/235-1572

Worldwide affiliates and phone numbers: Cherry Semiconductor Corp., East Greenwich, RI, U.S.A. 401-885-3800 • Cherry Mikroschalter GmbH, Auerbach, Germany, 09 843 181 • Cherry Electrical Products Ltd., Harpenden (Herts) England, (05827) 63100 • Chercro Brasil Industria E Comercio Ltda., Sao Paulo, Brazil, 55 (011) 248-4343 • Hirose Cherry Precision Co., Ltd., Kawasaki, Japan, 044 933 3511